

Item		(1)	(2)	(3)	(4)	(5)	New Land Cruiser /Land Cruiser Prado	Previous Land Cruiser /Land Cruiser Prado
Fuel System	HP3 type supply pump is used.	○	○	○			○	○
	A common-rail type fuel injection system is used.	○	○			○	○	○
	An injector on which compensation value and QR (Quick Response) code are printed is used.	○				○	○	○
	A fuel filter warning switch that detects the clogging of the fuel filter is used.				○		○	—
Charging System	Segment Conductor type alternator is used.			○			○	○
Serpentine Belt Drive System	A serpentine belt drive system is used.				○		○	○
Engine Control System	Non-contact type throttle position sensor is used.		○			○	○	—
	A pilot injection control system is used.	○	○			○	○	○
	EGR control system is used.					○	○	○
	An oil maintenance management system is used.				○		○	—

4. Cooling System

The thickness and fin pitch of the radiator have been changed, along with the increased power output of the engine.

► Specifications ◀

		New	Previous
Radiator Thickness	A/T	36 mm (1.42 in.)	24 mm (0.945 in.)
	M/T	24 mm (0.945 in.)	←
Radiator Fin Pitch	A/T	3.0 mm (0.118 in.)	←
	M/T	3.5 mm (0.138 in.)	4.0 mm (0.157 in.)